



*Engine instrumentation and electrical meters*  
*Custom engineered for bottom line performance*

# Bezel Options

BEZEL OPTIONS

Type	Gauge Size	Profile	3D Cut-away
<b>Radial</b>	2", 3", 5"		
<b>Euro</b>	2", 3", 5"		
<b>Low Profile</b>	2", 5"		
<b>Low Profile</b>	3"		
<b>High Profile</b>	<i>Contact Customer Service</i>		



ISO 9001 Certified  
CE • Q1 • QUEST • FMC

Finish	Colors	Available In		
		2"	3"	5"
Standard	black , white	●	●	●
Custom				
Powder Coat	red, blue, purple, green	●	●	●
Ionized	black, gold	●	●	●
Polished	stainless	●	●	●

(Custom Colors are available for painted and powder coated bezels)

### Lens Cover

Bezel Type	Flat	Dome
Radial	No	Yes
Euro	Yes	Yes
Low Profile	Yes	Yes

*Fog Resistant  
Lenses  
Available*

### ENVIRONMENTAL SPECIFICATIONS

**Temperature**

Operating: -20°F to +185°F (-30°C to 70°C)

**Shock**

50G, 9-13 ms half sine, 25 shocks in each of three orthogonal axes with no damage

**Vibration**

Two hours in each of three orthogonal axes: remains within initial shape.

**QUV Testing**

Meets ASTM G53-96, no loss in shade, color-gloss.

**Salt Spray**

Meets or exceeds ASTM 117-97, 200 hours.

**Adhesion**

ASTM D3359-95, exceeds 4B classification cross hatch test.

Bezels-0503

BEEDE ELECTRICAL INSTRUMENT CO., INC. • P.O. BOX 8910 • PENACOOK, NH 03303-8910  
TEL: 603-753-6362 • FAX 603-753-6201 • EMAIL: sales@beede.com • WEB SITE: http://www.beede.com

BEZEL OPTIONS